



° Stainless mounting screws & nuts recommended.
 ° M3 or 4/40 size screws required.
 ° Sealing washers provided.

SEE CUTOUT PARAMETERS
 ON FOLLOWING PAGE

PROPRIETARY NOTICE – PERMISSION IS HEREBY GRANTED TO USE THE CONFIDENTIAL INFORMATION ON THIS DOCUMENT FOR REFERENCE ONLY AND MAY NOT BE PRODUCED OR DISCLOSED TO OTHERS WITHOUT PRIOR WRITTEN PERMISSION OF MARINE PC.
UNLESS OTHERWISE SPECIFIED

TOLERANCES
 LINEAR X = ± .01
 ANGULAR ± .005

Project: **AWM15RF**
 Status: Released
 Design: EC Date: 7/21/2006
 Check: MG Date: 8/2/2006

Part#: **MPC-AWM15RF**
 Material:
 Finish:
 P:\AWM\AWM15R\Assemblies\AWM15R\AWM15R Display Flush Mounted Bezel.iam

Dwg # **O1306.10**
 Rev # **1.0**
 WGT.=

MPC-AWM15RF
 Display, Flush Mount AWM15R

Marine PC
 3420 North Stone Gully Mesa, Arizona 85207
 P: 480-515-1838 F: 480-515-0144